

			Ecocycle 13	Ecocycle 26	Ecocycle 39	Ecocycle 46
Hot Water	Capacity(1)	kW	13,72	26,24	39,24	46,03
	Power	kW	3,30	6,20	9,16	10,58
	COP(1)	W/W	4,15	4,20	4,28	4,35
Heating	Capacity(2)	kW	12,32	21,93	31,67	38,01
	Power	kW	2,90	5,10	7,40	8,80
	COP(2)	W/W	4,25	4,30	4,28	4,32
	Capacity(3)	kW	12,02	20,44	30,04	36,33
	Power	kW	3,70	6,10	9,05	10,75
	COP(3)		3,25	3,35	3,32	3,38
	Operating Temperature Range	°C	-10/+45			
	Max Outlet Water Temperature	°C	56			
Cooling	Capacity(4)	kW	9,28	15,53	22,39	26,75
	Power	kW	3,27	6,06	8,99	10,70
	EER	W/W	2,53	2,56	2,49	2,50
	Operating Temperature Range	°C	+24/+43			
	Min Outlet Water Temperature	°C	5			
Compressor	Type	Scroll				
	Refrigerant	R407C				
	Quantity	1				
Heat Exchanger	Type	Braze Plate Heat Exchanger				
Fan	Type	Axial				
	Brand	Rosenberg				
	Fan Speed		915-1015 rpm	620-850 rpm	670-880 rpm	670-880 rpm
	Sound Level		52 dB	55 dB	58 dB	58 dB
	Fan Motor Input Power		220-270 W	460-550 W	521-600 W	521-600 W
Dimensions	Width	mm	717	927	1027	1030
	Depth	mm	753	803	953	953
	Height	mm	803	1003	1003	1003
	Weight	kg	135	210	270	310
	Sound Level	dBA	62	64	68	68
Recirculation Pump	m³/h	2,5	4	6	6,5	
Device Pressure Loss	Kpa	30	40	50	55	
Cable Section	mm²	5x2,5	5x4	5x4	5x4	
Fuse	A	20	20	40	40	
(Input-Output) Pipe Diameter	mm²	1 1/4"				
Voltage	V/PH/HZ	380/3/50				
Additional Heater		Optional				
Automatic Defrost		Yes				
Low Pressure Protection System		Yes				
High Pressure Protection System		Yes				
(1) : Heating Power A20/W15-55 (In EN14551 measurement standards). Outside temperature DT 20 °C, WT 15 °C						
(2) : Heating Power A7/W35-30 (In EN14551 measurement standards). Outside temperature DT 7 °C, WT 6 °C						
(3) : Heating Power A7/W45-40 (In EN14551 measurement standards). Outside temperature DT 7 °C, WT 6 °C						
(4) : Cooling Power A35/W7-12 (In EN14551 measurement standards). Outside temperature 35 °C.						